

## Product Datasheet

Product ID: TP-ADAPTOR-EPMP



# TwistPort™ Adaptor for ePMP™ 1000

ADAPTOR FOR EPMP™ 1000 AP OR CSM

The TwistPort Adaptor for ePMP™ 1000 AP and CSM makes the ePMP™ 1000 series compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the ePMP™ 1000 AP or CSM into the TwistPort™ Adaptor is very simple and requires no tools.



### TECHNICAL DATA

Antenna Connection	TwistPort - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.5 Kg / 1.1 lbs* – single unit incl. package N/A – carton (units)
Single Unit	Retail Box: 12.8 x 13.6 x 11.7 cm*
N/A units	Carton Box: N/A

\*Estimation based on pre-production units. Subject to change.

### PERFORMANCE

Frequency Range	5400 - 5900 MHz
Polarization	Dual Linear H + V
Cross Pol Isolation (Min)	29 dB
VSWR Max	1.8
VSWR Typical	1.4
Impedance 50 Ohm	50 Ohm
Isolation Between Ports	37 dB

### COMPATIBLE WIRELESS PLATFORMS

RF elements®	any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna
Cambium Networks™	ePMP™ 1000 AP, ePMP™ 1000 CSM

### PACKAGE CONTENTS

TwistPort™ Adaptor

### PRODUCT DIMENSIONS

