

# NanoBracket® SXT 2.0

2ND GENERATION NANOBACKET FOR ROUTERBOARD™ SXT

NanoBracket® SXT 2.0 is 2nd generation of NanoBracket® for RB SXT. Improved 3-Axis Positioning System enables smooth adjustment of the RouterBoard™ SXT in azimuth, elevation and rotation.




Installation on the pole or on the wall is now even easier. NanoBracket® is built to last. The base of the bracket is made of diecasted aluminium, plastic parts are made of outdoor resistant ABS. All hardware is made of stainless steel.



## TECHNICAL DATA

Materials	Bracket - Diecasted Aluminum Holder - UV stabilized and weather resistant ABS plastic Hardware - Stainless Steel
Flame Rating	UL 94 HB
Pole Mounting Diameter	50-70 mm
Wall Mounting	Yes
Operating Temp.	-30 to +60 °C
Wind Survival	120 Km/h
Weight	0.33 Kg / 0.72 lbs – single unit incl. package 17.5 Kg / 38.6 lbs – carton (50 units)
Single Unit	Retail Box: 15 x 9 x 9 cm
50 units	Carton Box: 93 x 48 x 18 cm

## PRODUCT DIMENSIONS



## COMPATIBLE WIRELESS PLATFORMS

MikroTik™	RouterBoard™ SXT Lite5 RouterBoard™ SXT HG RouterBoard™ SXT SA RouterBoard™ SXT Lite2 RouterBoard™ SXT G-2HnD
-----------	---

## PACKAGE CONTENTS

- Bracket Body 1
- Bracket Body 2
- 2 x Screw M 2,9 x 16 mm
- 4 x Screw M 3,5 x 45 mm
- 4 x Wall Plug
- 1 x Hose Clamp

