

DH-PFS3106-4P-60

4-Port PoE Switch (Unmanaged)



Features

- > Two-layer industrial PoE switch
- > MAC auto study and aging, MAC address list capacity is 8K
- > Support IEEE802.3af, IEEE802.3at standard
- > Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- > Industrial wide temperature design

DH-PFS3106-4P-60

Technical Specifications

| Model | DH-PFS3106-4P-60 |
|------------------------|---|
| Ethernet Port | 1*100/1000 Base-X、 1*10/100/1000 Base-T、 4*10/100 Base-T (PoE power supply) |
| PoE Power Consumption | Each power $\leq 30W$, Total $\leq 60W$ |
| PoE Protocol | IEEE802.3af、IEEE802.3at |
| Switching Capacity | 6.8G |
| Packet Forwarding Rate | 3.57Mpps |
| Packet Buffer Memory | 1Mb |
| MAC Table Size | 8K |
| Flow Control | Enable by default |
| Application Humidity | 10%—90% |
| Power | Default DC53V power adapter |
| Lightning Protection | Common Mode 4KV Differential Mode 2KV |
| Working Temperature | - 30°C ~ 65°C |
| Weight | 480g |
| Dimension(W×D×H) | 150mm×100mm×30mm |

Accessories

| Model | |
|---------|--|
| PFT3900 | 155M 850nm,2km,LC, Multi-mode |
| PFT3950 | 1.25G 850nm,500m,LC, Multi-mode |
| PFT3910 | 155M 1310/1550nm,20km,LC, Single-mode |
| PFT3920 | 155M 1550/1310nm,20km,LC, Single-mode |
| PFT3960 | 1.25G 1310/1550nm,20km,LC, Single-mode |
| PFT3970 | 1.25G 1550/1310nm,20km,LC, Single-mode |

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815



DH-PFS3106-4P-60

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.